

CLAIMS

What is claimed is:

- sub 1
 1. A method for concealing errors in texture partition
 2 of a video packet, comprising:
 3 determining a particular macroblock within the texture
 4 partition where error is detected;
 5 concealing the error starting at the particular
 6 macroblock;
 7 evaluating image smoothness of concealed macroblocks;
 8 repeating said concealing and evaluating with one more
 9 macroblock added prior to the previous particular macroblock,
 10 said repeating done until all macroblocks in the texture
 11 partition have been concealed; and
 12 selecting a set of macroblocks, including a combination
 13 of decoded and concealed macroblocks, that produces best
 14 image smoothness.
- 1 2. The method of claim 1, further comprising:
 2 storing all decoded macroblocks of texture data in the
 3 texture partition up to the particular macroblock.

1 3. The method of claim 1, wherein said concealing the
2 error starting at the particular macroblock includes
3 performing motion compensated temporal replacements of
4 macroblocks starting at the particular macroblock.

A' Cont
1 4. The method of claim 3, wherein said performing
2 motion compensated temporal replacements is done for those
3 macroblocks whose motion vectors have changed.

1 5. The method of claim 1, wherein said evaluating
2 image smoothness of concealed macroblocks includes computing
3 smoothness of macroblock boundaries.

1 6. The method of claim 5, wherein said smoothness of
2 macroblock boundaries is measured by summing pixel value
3 mismatches between macroblock boundary pixels.

1 7. The method of claim 6, wherein said summing pixel
2 value mismatches includes storing partial mismatch values.

1 8. The method of claim 6, wherein said summing pixel
2 value mismatches includes summing squares of the pixel value
3 differences.

1 15. The method of claim 12, wherein said detecting
2 includes detecting receipt of out-of-range
3 motion vectors.

4 16. The method of claim 2, wherein said detecting
5 includes DCT coefficient counts greater than a
6 predetermined amount of approximately 64
7 pixels for a macroblok and Y/Cr/Cf pixel
8 values out of range.

1 17. The method of claim 2, wherein said selecting a set
2 of macroblocks includes recovering some of the stored decoded
3 macroblocks.

1 18. The method of claim 17, wherein said some of the
2 stored decoded macroblocks include decoded macroblocks up to
3 a macroblock that produced the best image smoothness.

1 19. A method for concealing errors in texture partition
2 of a video packet, comprising:

3 determining a particular location within the texture

4 partition where error is detected;

5 concealing the error in texture data starting at the
6 particular location;

7 evaluating image smoothness of the concealed texture
8 data;

9 repeating said concealing and evaluating with one more
10 texture data unit added prior to the previous particular
11 location, said repeating done until all texture data units in
12 the texture partition have been concealed; and

13 selecting a set of texture data units, including a
14 combination of decoded and concealed texture data units, that
15 produces best image smoothness.

1 20. The method of claim 19, wherein said concealing the
2 error in the texture data starting at the particular location
3 includes performing motion compensated temporal replacements
4 of texture data units starting at the particular location.

1 21. An error concealment system for texture partition
2 of a video packet, comprising:
3 an error location detector to receive video packets, and
4 determine a particular macroblock within the texture
5 partition where error is detected;
6 an error concealment element to conceal the error
7 starting at the particular macroblock;
8 an image smoothness evaluator to evaluate the concealed
9 macroblocks;
10 a selector to select a set of macroblocks, including a
11 combination of decoded and concealed macroblocks, that
12 produces best image smoothness.

1 22. The system of claim 21, wherein said error
2 concealment element includes a motion compensated temporal
3 replacement element.

1 23. The system of claim 21, further comprising:
2 a storage element to store all decoded macroblocks of
3 texture data in the texture partition up to the particular
4 macroblock.

Cont⁵/₆

[illegible]

```

9      evaluating image smoothness of concealed macroblocks;

```

```

10         repeating said concealing and evaluating with one more

```

14 selecting a set of macroblocks, including a combination
15 of decoded and concealed macroblocks, that produces best

1 25. The computer medium of claim 24, further
2 comprising:

```

3     storing all decoded macroblocks of texture data in the
4     texture partition up to the particular macroblock.

```